

Industrial HVAC is at its easiest when you have **support for life**

Whether you are contracting on a building or own the building itself, doing business with Cambridge feels easier. We are industry experts who guarantee your success. and are committed to **lifelong support for you, our customer.**

Energy Efficient

The most energy efficient industrial freeze protection technology on the market. Heating and ventilating building shells for future upgrades kickstart early energy savings for developers and owners.



Expert Support

We've strategically invested in a multi-layered team of expert engineers dedicated to resolving facility design challenges. Equipment designs and placement support ensures future upfit coordination for tenants.



Built to Last

Equipment that will work as expected for your facility's needs. Our freeze protection solution delivers reliable performance that meets building codes for your speculative build, thanks to our investment in top-tier precision metal works machinery, system software, and our Lean Manufacturing culture. Every unit also undergoes 100% testing, ensuring consistent performance and durability.

P

Short Lead Times

We offer the shortest lead times in the Industrial market with delivery dates you can rely on. Each order comes as a fully kitted package from units to curbs to accessories, reducing field labor cost and speeds up installation.



Spec Air Series

100% Outside Air Ventilation Unit

Commercial Applications

Aviation Agricultural Warehouse/Distribution Automotive Services and Repair Sports Arenas Greenhouses Municipality Retail Restaurants Parking Garages

Industrial Applications

Manufacturing Waste Water Treatment Warehouse Founderies Paint Booths







Spec Air Series 100% Outside Air Ventilation Unit

Features

Patented Low Fire Start technology increases reliability and saves energy

Proprietary high performance type 304 stainless steel burner

Two year parts warranty on the unit and exclusive five year burner warranty

Base Unit Specifications

Airflow Ranges: 6,000 - 34,000 CFM

V18	6,000–10,000 CFM
V20	10,000-17,000 CFM
V25	15,000-26,000 CFM
V30	22,000-34,000 CFM

Standard Features

Intake:

Dual rain hood Inlet screen

Discharge Options:

High velocity modular discharge nozzle (end-user configurable)

Options

Intake: V-bank filter section

Discharge Options: Motorized discharge damper

Gas Controls: High Pressure Regulator Mounting: Outdoor Roof top Discharge Down blast BTUS Ranges:

600 - 4,000

Motor Type:

Gas Controls:

Maxitrol Series 44/ modulating

Electrical Control

Remote control station

Exhaust fan contact/damper

ODP

controls

Options

Voltage 208/3/60

230/3/60 460/3/60

Casing/Finish

Single wall galvanized

14" Mounting Curbs

Filters Merv 8 Permanent pleated Aluminum

CAMBRIDGE AIR SOLUTIONS